


ES-8000T JUMBO



System description

- Storefront system rated for large and small missile impact.
 - Frame depth: 5".
 - Sight line: 2 3/4".
 - Designed for 1-5/16" insulated laminated glass.
- (Certifications might not consider every configuration).


Features

- Pre-assembled & pre-glazed.
- Reinforcement option available.
- Anodized, painted and wood grain finishes available.
- Thermally broken system.
- Single or multiple lites configurations available.


Test & Certifications

- Design loads: +70/-70 PSF.
 - Air infiltration: 13.5 PSF.
 - Water infiltration: 6.25 PSF.
 - STC: 37
 - (FBC/NOA)
- This data corresponds to the highest values obtained for some configurations. It can vary and may not apply to all.


Configurations



System details



Glazing options



- G1: 1/4" Hs Glass + 0.90" Interlayer Sentryglas + 1/4" Hs Glass + 1/2" Spacer + 1/4" Temp. Glass.
- G2: 1/4" Hs Glass + 0.90 PVB 0 SGP + 1/4" Hs Glass + 1/2" Spacer + 1/4" Temp. Glass

GLASS FINISH: PAINTED, SERIGRAPHY & DIGITAL PRINTED.

For more information please contact TECNOGLASS or visit www.tecnoglass.com

Aluminum

ALLOY 6063-T6
ALLOY 6005-T5

For further information about aluminum and finishes, consult ALUTIONS®.

Sealant

APPROVED SILICONE SEALS:

WEATHERPROOFING SILICONE:

Used to seal profile unions to avoid air and water infiltration.

STRUCTURAL SILICONE:

Besides acting as a sealant it is capable to support high loads. This silicone is commonly used to support the glass in facades and hurricane resistant products.

Measurements

Maximum size:

Single: Width 84", Height 180".

Single two lites: Width 102", Height 169 3/4".

Multiple with two lites: Width 305 1/8", Height 135 3/4".

Certifications might not consider every configuration. Tests values correspond to the best values obtained for some configurations; they can vary and may not apply to all. **VERIFY APPROVAL FOR EACH SPECIFIC CONFIGURATION.**